

????? LTE1101-G 12V ????????



?????????: ??? ??????????? ?????
????
????? ??? ?? ?? 14,59 €

???? ?? ?????? 11,77 €

???? ?????? ?? ??????

???? ?????? 14,59 €

???? ?????? ????? ??? 11,77 €

????????? ????? 2,82 €

[??????? ??? ?? ??????](#)

???????? - ?????: ????? LTE1101-G 12V ????????

????????????[Elmark](#)

????????

Technical characteristics:

- Rated voltage: 12/230V, 50/60 Hz;
- Insulation voltage: 660V, 50/60 Hz;
- Options for light and sound indication
- Impulse voltage withstand: 6000V
- Rated power: 6-28W
- Short circuit protection: 1A gG external fuse
- Operating temperature: -20°C - +70°C
- Humidity: 35-85% RH
- Plastic cover: UV resistant polycarbonate

Warning lights are offered individually in yellow, green and red colours, and the warning towers – in a combination of up to 5 colours: green, yellow, red, blue and white.

?????????: ?????? ??????????: **base_uom/descry** ?????: E1 ??????????: E177 ??????: 3+0 Three years standard, without extended

?????? ??????????: IP44

?????????? ?????: 12V

?????: 10W

?????: ???????

?????: ELMARK

?????: ?????

????????: 3+0