

?????????????? SPD-C10/1P 10KA



?????????????: ??? ?????????????? ?????
????
?????? ??? ? ? ? 15,20 €

???? ? ? ?????? 12,26 €

???? ?????? ? ? ??????

???? ?????? 15,20 €

???? ?????? ????? ? ? 12,26 €

????????? ????? 2,94 €

[???????? ? ? ? ??????](#)

??????????????? [Elmark](#)

??????????

Technical characteristics:

- Rated discharge current: 5-40??
- Rated operating voltage Uc: 275/440V,50Hz
- Number of poles: 1P; 1P+N; 3P; 3P+N
- Maximum discharge current : 10-60??
- Level of overload risk: B;C;D (from high to low risk level)
- Constant operating current:
up to 800?? for 1?, 2p and 3?
up to 600?? for 1?+N, 3p+N
- Ambient temperature: -10°÷65°?
- Installation altitude: up to 2000m

Mounting: Vertical on a DIN rail

Standards: EN61643-1

?????????????: ?????? ??????????: base_uom/descry ??????: E1 ??????????: E12311 ??????????: 7+0(I3) Seven years standard, without extended (3 years in

????????????? ?????: 275V

????????????? ?????: 10A

????????? ?????: 1

?????: ELMARK

????? ??????????: ?1,2 (kV)

?????????: 7+0

M?????: SPD